

# PRODUCT DATA SHEET

Infra**comfort**<sup>®</sup>

infrared heating

Supplier: Infracomfort NZ Limited  
 Email: derek@infracomfort.co.nz  
 Phone: 0274-775987 0800 386 374  
 Address: 8 Hurunui Lane, RD 1 Taupo 3377

BC FRAMELESS SERIES

Images

1. Dimensions: See models below
2. Rated voltage: 240V/50Hz
3. Heating element: Carbon crystal or NiCr (FW)
4. Wavelength: 8-15nm
5. Surface Temperature: 70-90°C
6. Electric Conversion efficiency: 98%
7. Life expectancy: >100,000 H
8. Front Surface: Powder coated Aluminium
9. Colour – Off white semi-gloss
10. Frame – no frame
11. Ingress protection ratio: IP42
12. Overheat protection: yes
13. Insulation: fully insulated back
14. Fitting: direct to ceiling or wall. Suspension **mount optional extra**
15. Cable length: 2m, rear entry
16. Standards: CE-LVD, EMC, RoHS, SAA



Rounded Corner

Model	Wattage	Dimensions (mm)			Weight (Kg)	Surface Colour
		Length	Width	Thickness		
FO606	280	595	595	25	4.1	Off white satin
F1006	450	1000	595	25	7.8	Off white satin
F1206	550	1195	595	25	8.1	Off white satin
F1006	700	1195	595	25	7.8	Off white satin
F1206	900	1195	595	25	8.1	Off white satin