

PRODUCT DATA SHEET

Infra**comfort**[®]

infrared heating

Supplier: Infracomfort NZ Limited
 Email: derek@infracomfort.co.nz
 Phone: 0274-775987 0800 386 374
 Address: 8 Hurunui Lane, RD 1 Taupo 3377

BC FRAMELESS SERIES

Images

1. Dimensions: See models below
2. Rated voltage: 240V/50Hz
3. Heating element: Carbon crystal or NiCr (FW)
4. Wavelength: 8,000-15,000nm
5. Surface Temperature: 70-90°C
6. Electric Conversion efficiency: 98%
7. Life expectancy: >100,000 H
8. Front Surface: Powder coated Aluminium
9. Colour – Off white semi-gloss/ Black semi gloss
10. Frame – no frame
11. Ingress protection ratio: IP42
12. Overheat protection: yes
13. Insulation: fully insulated back
14. Fitting: direct to ceiling or wall. Suspension **mount optional extra**
15. Cable length: 2m, rear entry
16. Standards: CE-LVD, EMC, RoHS, SAA



Rounded Corner

Model	Wattage	Dimensions (mm)			Weight (Kg)	Surface Colour
		Length	Width	Thickness		
FO606	280/450	595	595	25	4.1	* Off white satin
F1006	450	1000	595	25	7.8	Off white satin
F1206-5	550	1195	595	25	8.1	Off white satin
F1206-7	700	1195	595	25	7.8	Off white satin
F1206-9	900	1195	595	25	8.1	Off white satin

* Other colours are available on request