

infracomfort®

far-infrared heating



A Series / WIFI DATASHEET

derek@infracomfort.co.nz
 027 477 5987 or 0800 386 374
 18 Hurunui Lane, RD 1 Taupo 3377

A Series Specifications

- Rated voltage: 240V/50Hz
- Element: Carbon /NiCr WIRE Heating Wire
- Smart control: Wi-Fi enabled via Smart Life app and mobile phone. Optional connection to external thermostat.
- Wavelength: 8,000-15,000nm
- Surface Temperature: 95-110°C
- Electric Conversion efficiency: 98%
- Life expectancy: >100,000 H
- Front Surface: White Aluminium
- Frame: White or Black Aluminium
- Ingress protection ratio: IP52
- Overheat protection: yes
- Fitting: direct to ceiling or wall. Suspension mount optional extra
- Cable length: 2m, rear entry
- Standards: CE-LVD, EMC, RoHS, SAA



Elegant WiFi-enabled far-infrared heat panel available with black or white satin finish aluminium powder-coated frame. These far-infrared heat panels can be fixed directly to the ceiling or wall, fitted into suspended ceilings or lowered from high ceilings as required.

Model	Watts	Length (mm)	Width (mm)	Thickness (mm)	Weight (Kg)	Surface Colour	Frame Colour
A0706	320	695	595	20	3.9	White	White or black
A1206-5	700	1195	595	20	7.8	White	White or black
A1206-7	900	1195	595	20	8.1	White	White or black

FOR FREE INFRARED HEATING ASSESSMENTS CALL US TODAY ON 0800 386 374